

Republic of the Philippines Office of the Solicitor General Request for Quotation

Date:

Quotation #: ABC:

| To: | |
|-----------|---|
| Tel. No.: | |
| Fax No. | A |

Attention:

Sir/Madam:

Please quote your lowest price on the items/s listed below, stating the shortest time of delivery and submit this from duly signed by your representative.

RODRIGO L. OJENAL

SAO, Administrative Division

February 22, 2023

PS 023-02-029

To be filled-out by Supplier:

| TEM NO: | ITEM & DESCRIPTION | QTY | UNIT | BRAND | UNIT PRICE | TOTAL PRICE |
|---------|---|-----|------|-------|---------------|-------------|
| | Procurement of Electrical Supplies: | | | | | |
| 1 | THREE (3) GANG CONVENIENCE SURFACE OUTLET Blank; Can fit with switch and outlets Doesn't easily break; preferably with mounting screws | 100 | pcs | | | |
| 2 | ONE (1) GANG WIDE SERIES PLATE Blank; Can fit with switch and outlets Doesn't easily break; preferably with mounting screws | 50 | pcs | | | |
| 3 | TWO (2) GANG WIDE SERIES PLATE Blank; Can fit with switch and outlets Doesn't easily break; preferably with mounting screws | 100 | pcs | | | |
| 4 | SWITCH LIGHT (WIDE SERIES) Blank; Can fit with switch and outlets Doesn't easily break; preferably with mounting screws | 50 | pcs | | | |
| 5 | UNIVERSAL SOCKET OUTLET (WIDE SERIES) Operating Voltage: 250V-10amp; Highly insulating Flame Retardant; Heat resistant; Durable; | 100 | pcs | 2 | | |
| 6 | LED T8 Preferably Plastic TUBULAR LAMP DOUBLE ENDED Watts: 14-16 Watts DL; CT: 6500K; Bulb Material: Preferably Plastic Lumens: at least 1500lm; Original | 300 | pcs | | - | |
| 7 | LED TUBE ECOFIT T8 DAYLIGHT 600MM DOUBLE ENDED Watts: 8 Watts DL; CT: 6500K; Bulb Material: Preferably Plastic Lumens: at least 800lm; Original | 100 | pcs | | | |
| 8 | LED RECESSED CIRCULAR DOWNLIGHT Watts: 10 Watts Daylight; CT: 6500K; Voltage: 220V-240V Lumens: at least 850lm; Material: Preferably Plastic | 40 | pcs | | | |

| TEM NO: | ITEM & DESCRIPTION | QTY | UNIT | BRAND | UNIT PRICE | TOTAL PRICE |
|---------|--|-----|-------|-------|---------------|-------------|
| 9 | T5 ENERGY SAVING FLOURESCENT LAMP Watts: 14 Watts DL; CT: 6500K; Lumens: at least 1200lm; Material: Preferably Plastic | 30 | pcs | | | |
| 10 | LED A50 BULB E27 BASE Watts: 5.5 to 6 Watts DL; Voltage: 220 - 240V 50/60Hz Lumens: At least 550-600Im; Material: Preferably Plastic | 50 | pcs | | | |
| 11 | LED LITE A60 BULB E27 BASE Watts: 8-9 Watts DL; Voltage: 220 - 240V Lumens: At least 800lm; Material: Preferably Plastic | 50 | pcs | | | |
| 12 | COMPACT FLOURESCENT LAMP Watts: 14 Watts DL; Voltage: 220 - 240V Bulb Design 2U 2 pin; Bulb Type: Compact Flourescent Energy Saving; Lumens: At least 760lm; Material: Preferably Plastic | 50 | pcs | | | |
| 13 | CEILING RECEPTACLE FOR E27 WITH SCREW Ceiling Receptacle; With Screws; Cap: E27 Materials: Plastic/Aminoplastic; Diameter: 4 1/4" Voltage: 4A 250V | 50 | pcs | | | |
| 14 | PLUG-IN LAMPS 2 PIN, CFL Watts: 18 Watts; Daylight Bulb Design 2U 2 pin; Bulb Type: Compact Flourescent Lumens: at least 1200lm; Color Code: 865 | 50 | pcs | | | |
| 15 | FLAT CORD #16 WIRE Size (estimated): 16/2c (2 x 1.25mm ²) Usable length: at least 150m per roll; Rated Voltage: 300V Type: Flatcord Wire and Cable Type | 4 | rolls | | | |
| 16 | MALE PLUG; SWING TYPE (WITH SCREW) Voltage: 220V; Amperes: 10A; Heavy Duty | 40 | pcs | | | |
| 17 | STRANDED CORD #12 WIRE Type: Stranded Wire; Usable length: at least 150m per roll; Gauge: #12; (3.5mm ²); Can operate up to 600volts Material: Pure soft virgin copper (for 100% conductivity) Oil, Chemical, and Abrasion Resistant; Ampacity: 40amperes in air; 30 amperes in raceway Compliant with Philippine Electrical Code Requirements | 4 | rolls | | | |
| 18 | STRANDED CORD #14 WIRE Type: Stranded Wire; Usable length: at least 150m per roll; Gauge: #14; (2.0mm ²); Can operate up to 600volts Material: Pure soft virgin copper (for 100% conductivity) Oil, Chemical, and Abrasion Resistant; Ampacity: 35amperes in air; 25 amperes in raceway Compliant with Philippine Electrical Code Requirements | 4 | rolls | | | |
| 19 | 100 AMPERES 3 PHASE BREAKER (PLUG-IN) Ampere: 100 Amperes; 3 Pole 3 Phase Input Voltage: 100-240V | 5 | pcs | | | |
| 20 | 3 PHASE BREAKER (BOLT-ON) Ampere: 100 Amperes; 3 Pole 3 Phase Input Voltage: 100-240V | 10 | pcs | | | |

. .

| ITEM NO: | ITEM & DESCRIPTION | QTY | UNIT | BRAND | UNIT PRICE | TOTAL PRICE |
|----------|---|-----|------|-------|---------------|-------------|
| 21 | 30 AMPERES SINGLE PHASE CIRCUIT BREAKER (PLUG-IN) Type: Plug-in; Ampere: 30 Amperes; Input Voltage: 230V | 15 | pcs | | | |
| 22 | JUNCTION BOX (WITH COVER AND SCREW) Materials: Plastic/PVC; Flame Retardant With Cover and Screw; Color: Orange Note: Supplier must provide picture and model no. of the quoted items for technical evaluation of end-user. Winning supplier must warrant that in case of defective item upon usage, it will be subject for replacement. | 30 | pcs | | | |
| | (Price Vat-Included) | | | | | |

Delivery Period: Warranty: Price Validity:

SIGNATURE OF AUTHORIZED REPRESENTATIVE

Note:

1. Please quote within ____ days from the date of RFQ.

2. Bidders must submit current and valid documentary legal requirements upon sending the filled out quotation

a. [] Mayor's / Business Permit;

b. [] PhilGEPS Registration Number: _____ Membership: [] Platinum [] Red

c. [] Income / Business Tax Return (for Small Value Procurement, above Php500,000);

d. [] Omnibus Sworn Statement for Small Value Procurement (for above P50,000 - for unnotarized; Notarized OSS is required upon signing of PO);

e. [] Bidders who have previously submitted the above legal requirements may no longer require its re-submission.

Sir.

I hereby certify under oath that I have personally conducted this canvass, which the price/s quoted are true and correct, and the signature of representative of the company submitting the quotation is genuine.

Sabel ISRAEL C. DALLUAY

SIGNATURE OF CANVASSER

For more information, you may contact us:Telephone:8836-3314Telefax:8813-1174Please send your quotation to:

rfq.osgprocurement@gmail.com

OSG-HA-QF-039 Rev.00 (05 July 2018)