

## Republic of the Philippines Office of the Solicitor General

## Case Management Service

## **TERMS OF REFERENCE**

1.	ICT Equipment	Statement of Compliance
•	The Bidder must be an authorized reseller/authorized dealer of the brand being offered. A current valid manufacturer's certification required as part of the technical component on bid proposal for major components such as for Lot 1: Notebook PC, Mobile devices, Mini PC, Scanners, VOIP phones and Network Upgrade.	
•	The Bidder must not exceed to sixty (60) day delivery lead-time upon receipt of Notice to Proceed.	
•	Must attach brochure of the brand being offered.	
2.	For Corporate Notebook and Mini PC except high end notebook PC	
•	The Bidder must be an Authorized Service Partner (ASP) of the brand being offered and a current valid manufacturer certificate is required as part of the technical component on bid proposal.	
•	The Bidder must have at least two (2) manufacturer certified engineers for the brand of laptop and Mini PC. A current valid manufacturer certificate is required as part of the technical component on bid proposal.	
•	The brand which represents the bidder must apply in the latest top 3 of the Leaders Group of Gartner's List for Global Enterprise Notebook and Desktop. Certification in the inclusion in the Top 3 is required from the brand's manufacturer.	
•	Winning Bidder should replace a factory defective unit with a new unit within 30 days upon delivery of the item.	
•	In case of outside repair within the 3-year warranty period, the winning bidder shall provide a service unit to the OSG.	
•	For the two above items: Must submit Proof of warranty as part of the technical component.	
3.	High End Notebook PC	
•	Winning Bidder should replace a factory defective unit with a new unit within 30 days upon delivery of the item.	
•	In case of outside repair within the warranty period, the winning bidder shall provide a service unit to the OSG.	

•	Must submit Proof of warranty as part of the technical component.	
4.	Network Upgrade	
•	The brand being offered must belong to the Leaders Magic Quadrant for the Wired and Wireless LAN Access Infrastructure. (Please attach certificate)	
•	The bidder must be an authorized reseller/authorized dealer of the brand being offered. A current valid manufacturer's certificate must be submitted as part of the technical component on bid proposal.	

ICT EQUIPMENT - OFFICE PRODUCTIVITY (NEP)		
Item	Specifications	Statement of Compliance
FI	LE STORAGE FOR LEGAL DIVISIONS (10 Units)	
Technology	Must be High performance 2-bay NAS server	
Features	Must have High-speed data transfer and must be AES-NI	
	hardware encryption engine	
	Must be screw less drive bay design and hot-swappable	
	support	
	Must be dual core processor	
	Must have 4K Ultra HD video transcoding that allows you	
	to transcode H.264 4K videos to 1080p and stream them	
	to high-definition TVs, digital media players, mobile	
	handsets, and computers in the required format	
	Must have User Home feature that automatically create a	
	"home" folder for every user account	
	Must have Ultimate file center feature	
	Must be comprehensive network protocol support	
	including FTP, SMB2, AFP, NFS and WebDAV. With	
	Windows AD and LDAP integration	
	Must have Cloud Station Back up feature	
OS	Must include DiskStation Manager	
Specifications		
CPU	Intel Celeron N3060 Dual Core 1.6 burst up to 2.48 GHz	
	64 bit	
System	1GB	
Memory		
Storage	2 Drive Bays (Hot Swappable)	
	2 x 2TB NAS HDD, Interface : SATA 6Gb/s, Cache : 64MB,	
	Spin Speed : 5900RPM	
	* Max Sustained Data Transfer Rate OD (MB/s): 159	
	* Voltage Tolerance, Including Noise (5V): ±5%	
	* Voltage Tolerance, Including Noise (12V): ±10%	
	* Load/Unload tested to 600,000 cycles	
Compatible	3.5" SATA III / SATA II HDD	
Drive Type		

	2.5" SATA III / SATA II HDD	
	2.5" SATA III / SATA II SSD	
Supported RAID	Hybrid RAID	
Туре		
	Basic	
	JBOD	
	RAID 0	
	RAID 1	
RAID Migration	Basic to RAID 1	
File Sharing Capacity	Maximum Local User Accounts: 2048	
	Maximum Local Groups: 256	
	Maximum Shared Folder: 256	
	Maximum Shared Folder Sync Tasks: 4	
	Maximum Concurrent CIFS/AFP/FTP Connections: 256	
Snapshot Replication	Maximum Snapshots per Shared Folder: 256	
	Maximum Snapshots of all Shared Folder: 4096	
External Ports)	2 x USB 2.0 Port	
	1 x USB 3.0 Port	
	1 x eSATA Port	
_	USB Copy	
Size (Height x	165 mm x 108 mm x 233.2 mm	
Width x Depth)	4.25	
Weight	1.25 kg	
Warranty	One year on parts and labor	
	The bidder must be an authorized reseller of the brand being offered	
	CORPORATE NOTEBOOK PC (118 Units)	
Classification	True Branded Notebook PC	
Classification	Must belong in the top 3 of the Leaders Group of	
Certification	Gartner's Magic Quadrant for Global Enterprise Notebook	
	and Desktop (Must provide certificate)	
Processor	8th Generation Intel Core i5 Processor	
	i5-8250U (3.40 GHz Max. Turbo Frequency)	
Cache Memory	6 MB SmartCache	
Chipset	Intel SoC (System on Chip) platform	
Memory	8G (1X8GBDDR4 2400) On Board	
Max Memory	up to 20 GB of DDR4-2400Mhz, dual channel capable	
Graphics	AMD Radeon R17M-M1-70 GDDR5 2G	
	supports three independent displays;	
	Max resolution: 3840x2160@30Hz (HDMI);	
	1920x1200@60Hz (VGA)	
HDD	1TB 7MM 5400RPM	
Support HDD	Must Support Dual HDD (SSD + Traditional HDD)	
Display	14.0" (355mm) FHD TN (1920x1080) Anti-Glare, LED backlight, 220 nits, 16:9 aspect ration	

Connectivity	Integrated 10/100/1000 MBps Lan Controller; Wireless	
•	802.11 ac 1x1 and Bluetooth 4.1	
	Two USB 3.0 (one with optional Always On), one USB 3.1	
	Type-C Gen 1, one optional USB 3.1 Type-C Gen 1 (with	
Ports	the function of DisplayPort and PowerDelivery), one	
	optional USB 2.0 in Ultra-bay, VGA, HDMI, Ethernet (RJ-	
	45)	
Audio Support	HD Audio, Stereo speakers with Dolby® Audio™, 2W x 2	
Keyboard	6-row, spill-resistant, multimedia Fn keys	
Touchpad	One-piece touchpad, multi-touch	
	Security chip Fingerprint reader	
Security	Power-on password, hard disk password, supervisor	
	password, security keyhole	
Security Chip	Firmware TPM 2.0, integrated in chipset	
Fingerprint	Touch-type fingerprint reader	
Multimedia	Integrated Stereo Speakers, at least 0.3MP fixed focus,	
Options	physical camera shutter	
Operating	Windows 10 Pro Standard Preinstalled (Must provide	
System	certificate from the manufacturer that the OS installed is	
System	Genuine OS)	
Features	Sleek and robust design	
Color	Iron Gray	
Battery	2-cell 30Wh + 2-cell 39Wh Li-Polymer	
Adapter	BLACK 65W 3-PIN	
Carrying Case	Standard Carrying Case	
<b>B</b> :	WxDxH: 13.5" x 9.72" x 0.79"; 343mm x 247mm x	
Dimensions	20.3mm	
Maximum	Must be 1.05 kg / 4.07 lb	
Weight	Must be 1.85 kg / 4.07 lb	
Other	Must include branded MiniSaver™ lock	
	Must include an Optical Travel Mouse (same brand)	
	Must be 3 years warranty on parts and labor. (A valid	
Warranty	certificate issued by the manufacturer must be	
•	submitted).	
	EPEAT Silver; ENERGY STAR (A valid certificate issued by	
Environment	the manufacturer must be submitted) 6.1; RoHS-	
	compliant	
	The bidder must be an authorized reseller of the brand	
	being offered. Must provide Manufacturer certificate	
	HIGH END NOTEBOOK PC (35 Units)	
	Widescreen display	
	• 13.3-inch (diagonal) LED-backlit glossy widescreen	
<b>5</b> : 1	display with support for millions of colors	
Display	• Supported resolutions: 1440 by 900 (native), 1280 by	
	800, 1152 by 720, and 1024 by 640 pixels at 16:10	
	aspect ratio and 1024 by 768 and 800 by 600 pixels at	
	4:3 aspect ratio	
	aspect ratio	

Finish	Silver
	1.8GHz dual-core Intel Core i5, Turbo Boost up to
	2.9GHz, with 3MB shared L3 cache
Processor	
	Configurable to 2.2GHz dual-core Intel Core i7, Turbo
	Boost up to 3.2GHz, with 4MB shared L3 cache
Storago	128GB PCIe-based SSD
Storage	Configurable to 256GB or 512GB SSD
Memory	8GB of 1600MHz LPDDR3 onboard memory
	Up to 12 hours wireless web
	Up to 12 hours iTunes movie playback
Battery and	Up to 30 days of standby time
Power	Built-in 54-watt-hour lithium-polymer battery
	45W MagSafe 2 Power Adapter with cable
	management; MagSafe 2 power port
	• Height: 0.3–1.7 cm (0.11–0.68 inch)
Size and Weight	• Width: 32.5 cm (12.8 inches)
	• Depth: 22.7 cm (8.94 inches)
	Weight: 1.35 kg (2.96 pounds)
Graphics	Intel HD Graphics 6000
	Simultaneously supports full native resolution on the
	built-in display and up to 3840-by-2160 resolution at
Note: Comme	60Hz on an external display, both at millions of colors
Video Support	Thunderbolt digital video output  Native Mini Digale (Park autout)
	Native Mini DisplayPort output     NGA LIDML DVI and dual link DVI output using
	VGA, HDMI, DVI, and dual-link DVI output using adapters (available separately)
Camera	720p FaceTime HD camera
Camera	Two USB 3 ports (up to 5 Gbps)
Charging and	Thunderbolt 2 port (up to 20 Gbps)  Thunderbolt 2 port (up to 20 Gbps)
Expansion	MagSafe 2 power port
Expansion	SDXC card slot
	802.11ac Wi-Fi wireless networking; IEEE
Wireless	802.11a/b/g/n compatible
	Bluetooth 4.0 wireless technology
	Stereo speakers
Audio	Dual microphones
	3.5 mm headphone jack
	Full-size backlit keyboard with:
	78 (U.S.) or 79 (ISO) keys, including 12 function keys
	and 4 arrow keys (inverted "T" arrangement)
Keyboard and	Ambient light sensor
Trackpad	Multi-Touch trackpad for precise cursor control;
	supports inertial scrolling, pinch, rotate, swipe,
	three-finger swipe, four-finger swipe, tap, double-tap,
	and drag capabilities

	• Line voltage: 100, 240V AC	
	• Line voltage: 100–240V AC	
	• Frequency: 50Hz to 60Hz	
	Operating temperature: 10° to 35° C (50° to 95° F)	
Electrical and	• Storage temperature: -25° to 45° C (-13° to 113° F)	
Operating	Relative humidity: 0% to 90% noncondensing	
Requirements	Operating altitude: tested up to 3,000 meters (10,000)	
	feet)	
	Maximum storage altitude: 4,500 meters (15,000 feet)	
	Maximum shipping altitude: 10,500 meters (35,000)	
	feet)	
Operating	Original macOS	
System		
	Photos     iMaying	
	• iMovie	
	GarageBand	
	Pages	
	• Numbers	
	Keynote	
	Safari	
	Mail	
	FaceTime	
	Messages	
	• Maps	
Built-in Apps	• Stocks	
	• Home	
	Voice Memos	
	• Notes	
	Calendar	
	Contacts	
	Reminders	
	Photo Booth	
	Preview	
	• iTunes	
	Books	
	App Store	
	Time Machine	
	Accessibility features	
	Features include:	
	VoiceOver	
	• Zoom	
Accesibility	Increase Contrast	
	Reduce Motion	
	Dictation	
	Switch Control	
	Closed Captions	
	Text to Speech	
Warranty	Limited 90 days Telephone Support, 1 Year Warranty	

	Mobile Device 2 IN 1 TABLET (10 Units)	
Classification	Must be 2 in 1 Tablet	
Classification	Must be 10.1" IPS FHD display	
Dimension	Width (mm / inches) 256.6 / 10.1"	
Difficitation	Thickness (mm / inches) 9.6 / 0.38"	
	Height (mm / inches) 170.8 /6.72"	
Weight	690 g (1.52 lbs)	
Operating	030 g (1.32 103)	
System	Android™ 6.0.1 Marshmallow (upgradable)	
Processor	Intel® Atom™ x5-Z8550 Processor (2M Cache, Quad-Core,	
110003301	Up to 2.4 GHz)	
Sound	Dolby Atmos	
Memory	RAM (4 GB LPDDR3)	
	ROM (64 GB)	
	Card Slot (microSD™; Supports Up to 128 GB)	
Battery	Type : Li-ion Polymer	
	Capacity : 8500 mAh	
	Standby Time : Over 70 Days	
	General Usage : 15 Hours	
Display	Size: 10.1" FHD IPS (1920 x 1200)	
	Color Depth : 16.7 Million	
	Color Gamut : 70%	
	Brightness: 400 nits	
	Touch:	
	On Screen: Capacitive Touch with AnyPen Technology	
	Create Pad: Capacitive Touch and EMR Pen Technology	
	Material : Magnesium Aluminum Alloy	
Colors	Gunmetal Grey	
Connectivity	WLAN: WiFi 802.11 a/b/g/n/ac; Dual Channel (2.4 GHz and 5 GHz)	
Camera	Rear: 8 MP Auto-Focus	
Camera		
Keyboard	Front : 2 MP Fixed-Focus	
Sensors	Halo Keyboard Vibrator	
36113013	G-Sensor	
	E-Compass	
	Ambient Light Sensor Hall	
	Sensor	
	GPS A CRS	
Coffuera	A-GPS	
Software	Note Saver	
	Collection	
	SHAREit	
	SYNCit	
	Google Docs	
	Google Sheets	
	Google Slides	
	McAfee® Security	

	Evernote®	
	ArtRage TouchPal	
	IME	
Includes	Charger	
	USB Cable	
	Warranty Card	
	Quick Start Guide	
	Real Pen	
	Ink Cartridge Refills (3x)	
	Book Pad	
	Book Sleeve	
Warranty	Must be 1 year on parts and labor (on site)	
	The bidder must be an authorized reseller of the brand	
	being offered. Must provide Manufacturer certificate	
MII	NI PC FOR INTERACTIVE MONITORS (2 Units)	
Classification	True Branded Desktop PC	
	Must belong in the top 3 of the Leaders Group of	
Certification	Gartner's Magic Quadrant for Global Enterprise Notebook	
Certification	and Desktop (Must provide certificate)	
	Intel Core™ i3-8100T Processor (4 cores / 4 threads,	
Processor	3.1GHz)	
Cache Memory	6 MB Cache	
Chipset	Intel B360 Chipset	
Cilipset	4GB DDR4 2666, two 260-pin SO-DIMM sockets, dual-	
	channel capable	
Memory	*System automatically clocks down for the processors	
	with lower memory controller (32GB max)	
Graphics	Intel UHD Graphics 630	
HDD	1TB SATA 6.0Gb/s, 2.5" Wide, 5400 rpm	
1100	One USB 3.1 Gen1 (Always On and fast charge), one USB	
Front Ports	3.1 Type-C Gen 1, one microphone (3.5mm), one	
Tronc rones	headphone / microphone combo jack (3.5mm)	
	2x USB 3.1 Gen2, 2x USB 3.1 Gen1, 1x ethernet (RJ-45), 1x	
Rear Ports	DisplayPort, 1x HDMI, 1x Serial, 1x VGA	
Audio Support	Realtek ALC233VB2	
	Gigabit Ethernet, Intel Ethernet Connection I219-	
Ethernet	LM(Jacksonville), Wake on LAN	
Security chip	Discrete TPM 2.0, TCG Certified	
, , , , , , , , , , , , , , , , , , ,	Security slot (in rear for optional Kensington	
	MicroSaver cable)	
	Chassis intrusion switch	
	Power-on password	
Security	Administrator password	
features	Hard disk password	
	Boot sequence control	
	Boot without keyboard and mouse	
	Individual USB port disablement	
	Smart USB protection, allows keyboard/	
	- Smart oos protestion, anows keybourdy	

	manusa auto blasta all starage devises	
14 1 1	mouse only, blocks all storage devices	
Keyboard	USB Calliope Keyboard, black	
Mouse	USB Calliope Mouse, black	
Power Supply	65 watts AC/DC adapter, autosensing, 88% PSU	
	Tiny (1L), black color; metal case with VESA MOUNT	
Mechanical	Toolless chassis open (need optional toolless chassis	
Wicemanical	screw)	
	Toolless HDD, SSD, memory removal	
Environment	ENERGY STAR 7.0, EPEAT Gold rating (North America), ErP	
Liivii Oiliileiit	Lot 3, TCO, RoHS-compliant	
	Windows 10 Pro 64-bit Pre-installed (Must provide	
OS	certificate from the manufacturer that the OS installed is	
	Genuine OS)	
	Must be 3 years warranty on parts and labor. (A valid	
Warranty	certificate issued by the manufacturer must be	
	submitted).	
	The bidder must be an authorized reseller of the brand	
	being offered. Must provide Manufacturer certificate	
HI-RESC	DLUTION DOCUMENT SCANNER-75PPM (3 Units)	
Туре	Must be Desktop sheet-fed scanner	
Document		
Feeding	Must be Automatic or manual sheet feeding	
Document size		
Width	Must be 50.8 - 305mm	
Length	Must be 70 - 432mm	
Long Document		
Mode:	Must be up to 3,000mm	
Document		
thickness and		
weight		
Continuous		
Feeding	Must be 20 - 209g/m2, 0.04 - 0.25mm	
Non-Separation		
Mode	Must be 20 - 255 g/m2, 0.04 - 0.3mm	
Feeding		
Capacity	Must be 48mm stack or 500 sheets of 80 g/m2	
Scanning	AA	
Element	Must be 3-line CMOS CIS	
Light Source	Must be LED (red, green, and blue)	
Scanning Side	Must be Simplex / Duplex	
	Black and White, Error Diffusion, Advanced Text	
Scanning	Enhancement, Advanced Text Enhancement II, 256-level	
Modes	Grayscale, 24-bit Color, Auto Colour Detection	
Scanning		
Resolutions	150 x 150dpi, 200 x 200dpi, 240 x 240dpi, 300 x 300dpi,	
	400 x 400dpi, 600 x 600dpi	
Scanning	, ,	
speed*1 (A4 /		
LTR, 200dpi)		
,	I	

Γ		1
B&W	Portrait: DR-G1100: 75ppm (Simplex) / 150ipm (Duplex)	
	Landscape	
	Landscape: DR-G1100: 100ppm (Simplex) / 200ipm	
Cuevacale	(Duplex)	
Grayscale	Portrait: DR-G1100: 75ppm (Simplex) / 150ipm (Duplex)	
	Landscape: DR-G1100: 100ppm (Simplex) / 200ipm (Duplex)	
Colour	Portrait: DR-G1100: 75ppm (Simplex) / 150ipm (Duplex)	
Coloui	Landscape: DR-G1100: 100ppm (Simplex) / 200ipm	
	(Duplex)	
Interface	Hi-Speed USB 2.0	
Technical	opeda dos 2.0	
Specification		
Scanner driver	ISIS / TWAIN	
	Job Function, Ultrasonic Double-Feed Detection, Staple	
	Detection, Text Enhancement, Dropout and Color	
	Enhancement, Auto Page Size Detection, 3-D Color	
	Correction, Image Rotation, Skip Blank Page, Edge	
	Emphasis, Moiré Removal, Prevent Bleed Through /	
	Remove Background, Contrast Adjustment, Shading	
Useful functions	Correction, Brightness Adjustment, Deskew, Border	
	Removal, Scanning Side Selection, Scan Area Settings,	
	Add-on Settings, Text Orientation Recognition, Punch	
	Hole Removal, Folio Scan, Unnecessary dots removal,	
	Notch removal, Background Smoothing, Character	
	Emphasis, Count Only Mode, Verify Scan, Rapid Recovery	
	System, MultiStream™	
Power	AC220-240V (50 / 60Hz)	
requirements	AC220-240V (30 / 00112)	
Power	<b>220 - 240V:</b> 94.3W (Scanning), 1.7W (Sleep mode)	
Consumption	210 210 13 13 V (Scalling), 17 V (Sieep Hode)	
Operating	10 - 32.5°C	
Environment		
	Humidity: 20 - 80% RH	
Dimensions	Feed trays closed: 480 x 535 x 315mm	
(W x D x H)	A	
Weight	Approx. 22.8kg	
Warranty	Must be One year on parts and labor  The bidder must be an authorized reseller of the brand	
	being offered. Must provide Manufacturer certificate	
	VOIP PHONE WITH ADAPTOR (30 Units)	
Technology	Must be Business Media Phone	
	Must have 2 programmable lines/registrations	
	Must have 2.5" Graphical backlit LCD display with 5-way	
	navigation cluster for control	
	Must be HD voice and Acoustic Fence Technology	
	Must have 2 x Ethernet 10/100 for network pass through	
	Must have RJ9 Headset support with electronic hook	
	switch	
	SWITCH	1

	Must have full duplex Type 1-compliant speakerphone features	
	Must be designed for interoperability and is certified to	
	interoperate with the industry's broadest range of PBX	
	systems and SIP call control platforms	
	Must have Zero Touch Provisioning and web-based	
	configuration tool	
	Must be simple to deploy, easy to administer, upgrade,	
	and maintain	
User interface features	Must have Voicemail support	
	Reversible desk stand/wall mount	
	Unicode UTF-8-character support	
Feature Keys	4 context-sensitive "soft" keys	
•	2-line keys with bi-color (red/green) LED	
	"Home" feature key	
	4-way navigation key cluster with center "Select" key	
	2 volume control keys	
	Dedicated hold key	
	Dedicated headset key	
	Dedicated hands-free speakerphone key	
	Dedicated microphone mute key	
Call handling features	Shared call/bridged line appearance	
	Distinctive incoming call treatment/call waiting	
	Call timer and call waiting	
	Call transfer, hold, divert (forward), pickup	
	Called, calling, connected party information	
	Local three-way audio conferencing	
	One-touch speed dial, redial	
	Remote missed call notification	
	Do not disturb function	
	Electronic hook switch capable	
	Local configurable digit map/dial plan	
Network and provisioning	SIP Protocol Support	
	SDP	
	IETF SIP (RFC 3261 and companion RFCs)	
	Two-port Ethernet switch	
	10/100Base-TX across LAN and PC Ports	
	Manual or dynamic host configuration protocol (DHCP)	
	network setup	
	Time and date synchronization using SNTP	
	FTP/FTPS/TFTP/HTTP/HTTPS server based central	
	provisioning for mass deployments	
	Provisioning and call server redundancy supported	
	QoS Support–IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP	
	aliu uncr	

	Network Address Translation (NAT) – support for static	
	configuration and "Keep-Alive" SIP signaling	
	RTCP and RTP support	
	Event logging	
	Syslog	
	Hardware diagnostics	
	Status and statistics reporting	
Security	802.1X Authentication and EAPOL	
	Media encryption via SRTP	
	Transport Layer Security (TLS)	
	Encrypted configuration files	
	Digest authentication	
	Password login	
	Support for URL syntax with password for boot server	
	address	
	HTTPS secure provisioning	
	Support for signed software executables	
Power Adaptor	Must include External Universal AC Adapter 12V	
· orrei / taapto:	Must be One year with premier service program that	
	provides Service Partners with technical telephone	
	support, advance parts replacement, software upgrades	
Warranty	& updates, and access to Polycom's enhanced support	
	portal. The SLA must be included on the technical	
	requirements	
	The bidder must be an authorized reseller of the brand	
	being offered. Must provide Manufacturer certificate	
	WIRELESS BARCODE (5 Units)	
Technology		
10011101087	Must be 802.11b/g/n	
	, 5.	
	Must be rugged design	
Features	Must be rugged design  Must have flexible data capture options, a 1-D linear	
Features	Must be rugged design  Must have flexible data capture options, a 1-D linear imager, a 1-D laser and a 1-D and 2-D area imager kit, and	
Features	Must be rugged design  Must have flexible data capture options, a 1-D linear imager, a 1-D laser and a 1-D and 2-D area imager kit, and all three scan engines must capture damaged, dirty and	
Features	Must be rugged design  Must have flexible data capture options, a 1-D linear imager, a 1-D laser and a 1-D and 2-D area imager kit, and all three scan engines must capture damaged, dirty and scuffed bar codes on the first scan. QR Code Compatible.	
Features	Must be rugged design  Must have flexible data capture options, a 1-D linear imager, a 1-D laser and a 1-D and 2-D area imager kit, and all three scan engines must capture damaged, dirty and scuffed bar codes on the first scan. QR Code Compatible.  Must enterprise-grade push-to-talk (PTT), plus centralized	
Features	Must be rugged design  Must have flexible data capture options, a 1-D linear imager, a 1-D laser and a 1-D and 2-D area imager kit, and all three scan engines must capture damaged, dirty and scuffed bar codes on the first scan. QR Code Compatible.  Must enterprise-grade push-to-talk (PTT), plus centralized management features	
	Must be rugged design  Must have flexible data capture options, a 1-D linear imager, a 1-D laser and a 1-D and 2-D area imager kit, and all three scan engines must capture damaged, dirty and scuffed bar codes on the first scan. QR Code Compatible.  Must enterprise-grade push-to-talk (PTT), plus centralized management features  Must have RhocElements application development	
Development	Must be rugged design  Must have flexible data capture options, a 1-D linear imager, a 1-D laser and a 1-D and 2-D area imager kit, and all three scan engines must capture damaged, dirty and scuffed bar codes on the first scan. QR Code Compatible.  Must enterprise-grade push-to-talk (PTT), plus centralized management features  Must have RhocElements application development platform that allows you to create cross-platform	
	Must be rugged design  Must have flexible data capture options, a 1-D linear imager, a 1-D laser and a 1-D and 2-D area imager kit, and all three scan engines must capture damaged, dirty and scuffed bar codes on the first scan. QR Code Compatible.  Must enterprise-grade push-to-talk (PTT), plus centralized management features  Must have RhocElements application development platform that allows you to create cross-platform applications that work on different mobile computers	
Development Tools	Must be rugged design  Must have flexible data capture options, a 1-D linear imager, a 1-D laser and a 1-D and 2-D area imager kit, and all three scan engines must capture damaged, dirty and scuffed bar codes on the first scan. QR Code Compatible.  Must enterprise-grade push-to-talk (PTT), plus centralized management features  Must have RhocElements application development platform that allows you to create cross-platform	
Development	Must be rugged design  Must have flexible data capture options, a 1-D linear imager, a 1-D laser and a 1-D and 2-D area imager kit, and all three scan engines must capture damaged, dirty and scuffed bar codes on the first scan. QR Code Compatible.  Must enterprise-grade push-to-talk (PTT), plus centralized management features  Must have RhocElements application development platform that allows you to create cross-platform applications that work on different mobile computers with different operating systems	
Development Tools	Must be rugged design  Must have flexible data capture options, a 1-D linear imager, a 1-D laser and a 1-D and 2-D area imager kit, and all three scan engines must capture damaged, dirty and scuffed bar codes on the first scan. QR Code Compatible.  Must enterprise-grade push-to-talk (PTT), plus centralized management features  Must have RhocElements application development platform that allows you to create cross-platform applications that work on different mobile computers	
Development Tools	Must be rugged design  Must have flexible data capture options, a 1-D linear imager, a 1-D laser and a 1-D and 2-D area imager kit, and all three scan engines must capture damaged, dirty and scuffed bar codes on the first scan. QR Code Compatible.  Must enterprise-grade push-to-talk (PTT), plus centralized management features  Must have RhocElements application development platform that allows you to create cross-platform applications that work on different mobile computers with different operating systems  Must have 27-key numeric; 2 programmable side buttons	
Development Tools	Must be rugged design  Must have flexible data capture options, a 1-D linear imager, a 1-D laser and a 1-D and 2-D area imager kit, and all three scan engines must capture damaged, dirty and scuffed bar codes on the first scan. QR Code Compatible.  Must enterprise-grade push-to-talk (PTT), plus centralized management features  Must have RhocElements application development platform that allows you to create cross-platform applications that work on different mobile computers with different operating systems  Must have 27-key numeric; 2 programmable side buttons  Must support keypad overlays for localisation and custom	
Development Tools	Must be rugged design  Must have flexible data capture options, a 1-D linear imager, a 1-D laser and a 1-D and 2-D area imager kit, and all three scan engines must capture damaged, dirty and scuffed bar codes on the first scan. QR Code Compatible.  Must enterprise-grade push-to-talk (PTT), plus centralized management features  Must have RhocElements application development platform that allows you to create cross-platform applications that work on different mobile computers with different operating systems  Must have 27-key numeric; 2 programmable side buttons  Must support keypad overlays for localisation and custom functions	
Development Tools Keypad	Must be rugged design  Must have flexible data capture options, a 1-D linear imager, a 1-D laser and a 1-D and 2-D area imager kit, and all three scan engines must capture damaged, dirty and scuffed bar codes on the first scan. QR Code Compatible.  Must enterprise-grade push-to-talk (PTT), plus centralized management features  Must have RhocElements application development platform that allows you to create cross-platform applications that work on different mobile computers with different operating systems  Must have 27-key numeric; 2 programmable side buttons  Must support keypad overlays for localisation and custom functions  Must support HTML5	
Development Tools Keypad	Must be rugged design  Must have flexible data capture options, a 1-D linear imager, a 1-D laser and a 1-D and 2-D area imager kit, and all three scan engines must capture damaged, dirty and scuffed bar codes on the first scan. QR Code Compatible.  Must enterprise-grade push-to-talk (PTT), plus centralized management features  Must have RhocElements application development platform that allows you to create cross-platform applications that work on different mobile computers with different operating systems  Must have 27-key numeric; 2 programmable side buttons  Must support keypad overlays for localisation and custom functions  Must support HTML5  Must have Mobile Device Management (MDM) solutions	
Development Tools Keypad	Must be rugged design  Must have flexible data capture options, a 1-D linear imager, a 1-D laser and a 1-D and 2-D area imager kit, and all three scan engines must capture damaged, dirty and scuffed bar codes on the first scan. QR Code Compatible.  Must enterprise-grade push-to-talk (PTT), plus centralized management features  Must have RhocElements application development platform that allows you to create cross-platform applications that work on different mobile computers with different operating systems  Must have 27-key numeric; 2 programmable side buttons  Must support keypad overlays for localisation and custom functions  Must support HTML5	

Display	Must be 2.8 inches QVGA with backlight; TFT-LCD,64K colours	
Touchpanel	Must be Resistive touch panel	
-	Must have User accessible Micro SDHC card slot (up to	
Expansion Slot	32GB)	
Connectivity	Must have Bluetooth; USB 1.1 full speed host/client	
Notification	Must have LED and audible alert	
CPU	Marvell PXA 320 624 MHz	
Operating System	Microsoft Embedded CE 6.0 Pro	
Memory	256 MB/256 MB ROM	
Battery	2400 mAh rechargeable Smart Li-Ion; user replaceable	
Exit Window	Corning Gorilla Glass	
WLAN Security	WEP, WPA, WPA2, 802.1x, EAP-TLS,TTLS (CHAP, MS-CHAP, MS-CHAPv2, PAP or MD5), PEAP (TLS, MSCHAPv2, EAP-GTC), LEAP, EAP-FAST (TLS, MS-CHAPv2, EAP-GTC), CCXv4 certified	
WPAN	Bluetooth Class II, v 2.0 with EDR; integrated antenna	
Accessories	Must include handstrap, active sync cable, and power supply	
	Must include US AC line cord, 7.5 feet long, grounded,	
	three wire for power supplies	
Warranty	One year on parts and labor	
	The bidder must be an authorized reseller of the brand	
	being offered. Must provide Manufacturer certificate	
NETWORK A	ATTACHED STORAGE FOR BACKUP AND REPLICATION (1 Unit)	
HARDWARE	(1 omi)	
TITAL STATE		
СРИ	Intel Atom C2538 Quad Core 2.4GHz	
Hardware		
Encryption	Yes (AES-NI)	
Engine	( = 1)	
Liigiiic		
Floating Point	Yes	
RAM Size	DDR3 2 GB (Expandable up to 6 GB)	
Internal HDD/SSD	8 x 4TB 3.5" SATA 7200rpm	
Max Internal Capacity	48 TB (6 TB HDD X 8)	
Hot Swappable HDD	Yes	

Size (HxWxD) 157 x 340 x 233	
Size (HxWxD) 157 x 340 x 233	
	mm
Weight 5.29 kg	
LAN Gigabit X 4	
Wake on Yes	
Wireless Support	
Power 50 Hz to 60 Hz,	Single Phase
GENERAL	
	FTP, WebDAV, CalDAV, iSCSI, Telnet, SSH, TP, OpenVPN™, L2TP)
File System Internal: EXT4	
External: EXT4,	EXT3, FAT, NTFS, HFS+
	n Size: 108 TB, Max Internal Volume #: Target #: 32, Max iSCSI LUN#: 256;
Synology Hybri	pshot support; Supported RAID Type: d RAID, Basic, JBOD, RAID 0, RAID 1, RAID 10; Synology Expansion Unit Support:
File Sharing	unt: 2048, Max Group: 256, Max Shared ax Concurrent CIFS/AFP/FTP Connections:
Privilege Windows Acces	s Control List (ACL)
	tegration: Domain Users login via Samba /File Station, LDAP Integration
Virtualization VMware vSphe	re 5, Microsoft Hyper-V, Citrix Ready
Security	S, IP Auto-Block, Firewall, Encrypted p over Rsync, HTTPS Connection

Supported	Windows XP onward, Mac OS X 10.5 onward, Ubuntu	
Clients	9.04 onward	
Supported	Chrome ® , Firefox ® Internet Explorer ® : 8 or onward,	
Browsers	Safari <sup>®</sup> 5 or onward, Safari (iOS 5 or later on iPad <sup>®</sup> ),	
	Chrome (Android™ 4.0 on tablets)	
APPLICATIONS		
File Station	Virtual Drive, Remote Folder	
Backup	Network Backup, Local Backup, Desktop Backup, Shared	
Solutions	Folder Sync - Max Task Number: 8,	
	Configuration Backup	
Mail Server	Supported Mail Server Protocols: POP3, SMTP, IMAP	
ETD Co	Bandwidth Control, Custom FTP Passive Port Range,	
FTP Server	Anonymous FTP, Transfer Log	
Web Station	Virtual Host (up to 30 websites), PHP/MySQL ® , 3rd-Party	
	Applications Support	
	Max Printer #: 2, Printing Protocols: LPR, CIFS, IPP, Apple	
Printer Server	iOS Printing, Google Cloud Print™, Multi-Functional Print	
	Server (MFP functions are for Windows PC only)	
	SSL Connection, Log Rotation: 6 months, 1 year, 2 years, 3	
Log Center	years, Email Notification	
iOS/Android™	DS audio, DS cam, DS cloud, DS download, DS file, DS	
Applications	finder, DS photo+, DS video, DS note	
Windows™	DC audia DC danualand DC fila DC finday DC abata, DC	
Phone	DS audio, DS download, DS file, DS finder, DS photo+, DS video	
Applications	video	
Warranty	One year on parts and labor	
	The bidder must be an authorized reseller of the brand	
	being offered.	
Network Uplink l	Jpgrade to 10GB	
Item	Specifications	Statement of Compliance
Access S	witches POE with 2x 10G Copper Uplink (33 Units)	
Specifications	Must be Fixed port switch	

	Must have 24 RJ-45 auto-negotiating 10/100/1000 PoE+	
	ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type	
	100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3af	
	PoE, IEEE 802.3at.)	
	Must have 2 fixed 1000/10000 SFP+ ports	
	Must have 2 RJ-45 1/10GBASE-T ports	
	Must have 1 RJ-45 console port to access limited CLI port	
	Must have 128 MB flash; Packet buffer size: 1.5 MB, 1 GB	
	SDRAM	
	Mounting: Mounts in an EIA-standard 19 in. telco rack or	
	equipment	
	Must have 100 Mb Latency < 5 μs	
	Must have 1000 Mb Latency < 5 μs	
	Must have 10 Gbps Latency < 1.5 μs	
	Must have Throughput of up to 95.2 Mpps (64-byte	
	packets)	
	Must have Switching Capacity of 128 Gbps	
	Must have Routing Table Size: 32 entries (IPv4), 32	
	entries (IPv6)	
	Must have MAC Address Table Size : 16384 entries	
	Must be Voltage 100-240 VAC	
	Must be Frequency: 50/60 Hz	
	Must have Maximum Power Consumption of 425 W	
Warranty	Must be lifetime warranty on parts and one year on labor	
	on site	
	The brand being offered must belong to the Leaders	
	Magic Quadrant for the Wired and Wireless LAN Access	
	Infrastructure. (Please attach certificate)	
	The bidder must be an authorized reseller/authorized	
	dealer of the brand being offered. A current valid	
	manufacturer's certificate must be submitted as part of	
	the technical component on bid proposal.	
	MODULE FOR OSG and APMC Core Switch (8 ports 10G	
Co	opper for Distribution switch uplink) 3 Units	
• • • • • •	The second second second	
Specifications	Must be compatible to OSG's existing Core Switch	
	Must be 8 Ports multigig modules	
	Must be 1/2.5/5/XGT PoE+	
	Must be Lifetime warranty on parts and one year on labor	
	on site	
	The brand being offered must belong to the Leaders	
	Magic Quadrant for the Wired and Wireless LAN Access	
	Infrastructure. (Please attach certificate)	
	The bidder must be an authorized reseller/authorized	
	dealer of the brand being offered. A current valid	
	manufacturer's certificate must be submitted as part of	
	the technical component on bid proposal.	
	OG COPPER DISTRIBUTION SWITCH (1 Unit)	
Specifications	Must be high performance switching	

	Must be fixed port 10G Copper switch	
	Must have 32 RJ-45 1/10GBASE-T ports; Duplex:	
	100BASE-TX/1000BASE-TX/10GBASE-TX: Full Only	
	Must have 2 QSFP+ 40-GbE ports	
	Must have 8 fixed 1000/10000 SFP+ ports	
	Must be Layer 3 Dynamic	
	Must be 17.32(w) x 25.98(d) x 1.72(h) in (43.99 x 65.99 x	
	4.37 cm) (1U height)	
	Must be 28.66 lb (13 kg)	
	Must have 1 RJ-45 serial console port	
	Must have 1 RJ-45 out-of-band management port	
	Must have 1 USB 2.0"	
	Must have 2 power supply slots	
	Must have 512 MB flash, 2 GB SDRAM; packet buffer size: 9 MB	
	Mounts in an EIA standard 19-in. telco rack or equipment cabinet (hardware included)	
	Must have 10 Gbps Latency < 1.5 μs (64-byte packets)	
	Must have Throughput of 714.2 Mpps (64-byte packets)	
	Must have Switching Capacity of 960 Gbps	
	Routing Table Size: 128 entries (IPv4), 128 entries (IPv6)	
	MAC Address Table Size: 128,000 entries	
	Must be Voltage: 100 - 240 VAC	
	-48 to -60 VDC"	
	Frequency: 50/60 Hz	
	Maximum Power Consumption must be 350 W	
	Must include 2 x 650W AC Power Supply	
	Must include 2 x HV Fan Tray	
	Must be 1 Year warranty on parts and labor	
	Must include 3Y Foundation Care Next Business Day	
	Support	
	The brand being offered must belong to the Leaders	
	Magic Quadrant for the Wired and Wireless LAN Access	
	Infrastructure. (Please attach certificate)	
	The bidder must be an authorized reseller/authorized	
	dealer of the brand being offered. A current valid	
	manufacturer's certificate must be submitted as part of	
	the technical component on bid proposal.	
	IMPLEMENTATION SERVICES (1 Lot)	
Scope of Works	1. Install, Start-Up and Configuration	
	a. Physical Checking Installation	
	i. Pre-staging	
	ii. Hardware Testing	
	iii. Rack mounting	
	iv. Inserting/connecting power supplies	
	v. Power-up	
	b. Management	
	i. Creation of management VLAN	

ii. Assigning of management IP address per switch or
per stacked of switches
c. VLAN Configuration
i. Configuration of VLANS
ii. Configuration of Tagged port (VLAN up links)
iii. Configuration of inter-VLAN routing
d. Perform the following testing
i. Inter VLAN connection

Prepared by:

**AMELITO V. DUCUT** IT OFFICER III - COMD